



Tube PROGEF Standard S5/SDR11 (PN 10)

Exécution:

- Material: PP-H - homopolymer
- Dimension: acc. to DIN 8077/78
- Colour: light grey RAL 7032
- Pipe length: 5000mm, with plain ends
- **Note 1:** acc. to EN 15494
- **Note 2:** DIBT Z-40.23-4 approval
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentaion). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

Note	PN (bar)	d (mm)	Code	poids (kg/m)	di (mm)	e (mm)	pouce (inch)	
	1, 2	10	16	167 480 710	0,080	12,4	1,8	3/8
*	2	10	20	167 480 711	0,107	16,2	1,9	1/2
*	2	10	25	167 480 712	0,164	20,4	2,3	3/4
	2	10	32	167 480 713	0,261	26,2	2,9	1
	2	10	40	167 480 714	0,412	32,6	3,7	1 1/4
	2	10	50	167 480 715	0,638	40,8	4,6	1 1/2
	2	10	63	167 480 716	1,010	51,4	5,8	2
	2	10	75	167 480 717	1,410	61,4	6,8	2 1/2
	2	10	90	167 480 718	2,030	73,6	8,2	3
	2	10	110	167 480 719	3,010	90,0	10,0	4
	2	10	125	167 480 720	3,910	102,2	11,4	4 1/2
	2	10	140	167 480 721	4,870	114,6	12,7	5
	2	10	160	167 480 722	6,380	130,8	14,6	6
		10	180	167 480 723	8,070	147,2	16,4	7
		10	200	167 480 724	9,950	163,6	18,2	8
		10	225	167 480 725	12,600	184,0	20,5	9
		10	250	167 480 726	15,500	204,6	22,7	10
		10	280	167 480 727	19,400	229,2	25,4	11
		10	315	167 480 728	24,600	257,8	28,6	12
		10	355	167 480 729	31,200	290,6	32,2	14
		10	400	167 480 730	39,600	327,4	36,3	16

Les données techniques ne sont pas des "contraintes techniques". Elles ne représentent aucune caractéristiques garanties ni ne garantissent aucune propriétés d'une durabilité garantie . Elles sont soumises à des modifications . Nos conditions générales de vente sont applicables.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>