


Data sheet

valid from: 8/13/19



Tee 90° ABS metric

- >d225 - maximum operating temperature: +40°C



PN (bar)	d (inch)	d (mm)	Code	SP	Weight (kg)	closest inch (inch)	z (mm)	D (mm)	L (mm)
16		20	729 200 106	10	0.015	½	11	25	27
16		25	729 200 107	10	0.025	¾	14	31	33
10		32	729 200 108	10	0.042	1	17	40	39
10		40	729 200 109	10	0.078	1 ¼	21	49	47
10		50	729 200 110	5	0.134	1 ½	26	61	57
10		63	729 200 111	5	0.255	2	34	76	72
10	2 ½	75	729 200 112	6	0.404	2 ½	40	90	84
10		90	729 200 113	4	0.664	3	47	107	98
10		110	729 200 114	6	1.010	4	55	133	116
10	5	140	729 200 116	1	2.570	5	71	169	147
10		160	729 200 117	1	3.752	6	81	193	167
10		200	729 200 119	1	4.446	8	101	225	207
10		225	729 200 120	1	6.860	8	114	256	233
6		250	729 200 121	1	11.189	9	132	282	263
6		280	729 200 122	1	11.989	10	152	318	298
6		315	729 200 123	1	20.000	12	168	356	332

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>