



**Installation fitting type 312 PVC-U**  
**Glue on saddle metric**

**Model:**

- Top saddle for solvent cement bonding
- Saddle with threaded outlet 1 1/4" NPSM

**Range of use:**

- Compatible Signet flow sensors: type 2551, 2537, 515, 8510, 2536, 8512

**Attention:**

- sensor length depends on installation fitting

PN (bar)	DN (mm)	d (mm)	Code	SP	Weight (kg)	D (mm)	Sensor Type	H (mm)
10	65	75	<b>721 312 012</b>	1	0.220	38	flow X1	89
10	80	90	<b>721 312 013</b>	1	0.228	38	flow X1	89
10	100	110	<b>721 312 014</b>	1	0.225	38	flow X1	89
10	100	125	<b>721 312 015</b>	1	0.218	38	flow X1	81
10	125	140	<b>721 312 016</b>	1	0.213	38	flow X1	79
10	150	160	<b>721 312 017</b>	1	0.217	38	flow X1	76
10	200	200	<b>721 312 019</b>	1	0.192	38	flow X1	69
10	200	225	<b>721 312 020</b>	1	0.297	38	flow X2	141
10	250	250	<b>721 312 021</b>	1	0.295	38	flow X2	137
10	300	315	<b>721 312 023</b>	1	0.290	38	flow X2	127

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>