



ecoFIT pipe
SDR11/PN16/S5

Model:

- Material: PE100
- Dimension: acc. to DIN 8074/75
- Colour: black
- Pipe length: 5m, with plain ends
- **Note 1:** DIBT Z-40.23-406 Approval
- Attention: Pressure rates refer to operating temperatures at 20°C. Higher temperatures and aggressive flow media reduce pressure load (see above DIN and our technical documentation). Pressure load capacity has to be determined in consideration with safety demands of the respective applications and calculated in accordance.

Note	d (mm)	SDR	PN (bar)	Code	Weight (kg/m)	e (mm)	di (mm)
1	16	11	16	193 017 155	0.084	1.8	12.4
*	1	20	11	193 017 156	0.118	2.0	16.2
*	1	25	11	193 017 157	0.173	2.3	20.4
	1	32	11	193 017 158	0.282	3.0	26.2
	1	40	11	193 017 159	0.434	3.7	32.6
	1	50	11	193 017 160	0.673	4.6	40.8
	1	63	11	193 017 161	1.060	5.8	51.4
	1	75	11	193 017 162	1.480	6.8	61.4
	1	90	11	193 017 163	2.140	8.2	73.6
	1	110	11	193 017 164	3.180	10.0	90.0
	1	125	11	193 017 165	4.120	11.4	102.8
	1	140	11	193 017 166	5.130	12.7	114.6
	1	160	11	193 017 167	6.740	14.6	130.8
	1	180	11	193 017 168	8.510	16.4	147.2
	1	200	11	193 017 169	10.500	18.2	163.6
	1	225	11	193 017 170	13.300	20.5	184.0
		250	11	193 017 171	16.300	22.7	204.6
		280	11	193 017 172	20.500	25.4	229.2
		315	11	193 017 173	25.900	28.6	257.8
		355	11	193 017 174	32.900	32.2	290.6
		400	11	193 017 175	41.700	36.3	327.4
		450	11	193 017 176	52.800	40.9	368.2
		500	11	193 017 177	65.200	45.4	409.2

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>