




## Adaptor bush equal PVC-U metric R

### Model:

- With solvent cement socket metric and taper male thread R
- Install with low mechanical stress and avoid large cyclic temperature changes
- Do not use thread sealing pastes that are harmful to PVC-U



d (inch)	Thread Type	Size (inch)	d (mm)	PN (bar)	Code	SP	Weight (kg)	z (mm)	L (mm)	s (mm)
3/8	R	3/8	16	16	<b>721 910 705</b>	10	0.011	20	34	27
1/2	R	1/2	20	16	<b>721 910 706</b>	10	0.018	24	40	32
3/4	R	3/4	25	16	<b>721 910 707</b>	10	0.025	25	44	36
1	R	1	32	16	<b>721 910 708</b>	10	0.039	28	50	46
1 1/4	R	1 1/4	40	16	<b>721 910 709</b>	10	0.061	31	57	55
1 1/2	R	1 1/2	50	16	<b>721 910 710</b>	10	0.092	32	63	65
2	R	2	63	16	<b>721 910 711</b>	5	0.161	38	76	80
2 1/2	R	2 1/2	75	10	<b>721 910 712</b>	6	0.227	42	86	90
3	R	3	90	10	<b>721 910 713</b>	5	0.389	46	97	110
4	R	4	110	10	<b>721 910 714</b>	5	0.572	53	114	130

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: [info.ps@georgfischer.com](mailto:info.ps@georgfischer.com)

Internet: <http://www.gfps.com>