



Type 2551 Magmeter; Display Version with relays Current output (4 to 20 mA)

Flow:

- Installs into pipe sizes: DN15 to DN900, 0.5 to 36 in
- Operating range: 0.05 to 10 m/s, 0.15 to 33 ft/s
- Max Pressure rating: PP 10.3 bar @ 25 °C, 150 psi @ 77 °F
- Power source: 4 to 20mA, 21.6 to 26.4 VDC, 22.1mA maxAux Power for relays, 9 to 24 VDC, 0.4A max
- *Only Signet installation fittings

MFR #	Body	Electrode	Pipe Size (inch)	Sensor Type	Code
3-2551-P0-22	PP	316L SS	1 - 4	-X0	159 001 273
3-2551-P1-22	PP	316L SS	5 - 8	-X1	159 001 274
3-2551-P2-22	PP	316L SS	10 - 36	-X2	159 001 438
3-2551-T0-22	PVDF	Titanium	1 - 4	-X0	159 001 439
3-2551-T1-22	PVDF	Titanium	5 - 8	-X1	159 001 440
3-2551-T2-22	PVDF	Titanium	10 - 36	-X2	159 001 455
3-2551-V0-22	PVDF	Hastelloy C	1 - 4	-X0	159 001 275
3-2551-V1-22	PVDF	Hastelloy C	5 - 8	-X1	159 001 276
3-2551-V2-22	PVDF	Hastelloy C	10 - 36	-X2	159 001 457

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland

Phone +41 -(0)52-631 1111

e-mail: info.ps@georgfischer.com

Internet: <http://www.gfps.com>