


Coudes 45°, ABS métrique



• Pour diam >225, température max. +40°

Pouces [inch]	d [mm]	PN [bar]	Code	SP	poids [kg]	pouce [inch]	z [mm]	D [mm]	L [mm]
2 ½	20	16	729 150 106	10	0,009	½	5	25	21
	25	16	729 150 107	10	0,013	¾	6	31	25
	32	10	729 150 108	10	0,026	1	8	40	30
	40	10	729 150 109	10	0,044	1 ¼	10	49	36
	50	10	729 150 110	5	0,079	1 ½	12	61	43
	63	10	729 150 111	10	0,143	2	14	76	52
	75	10	729 150 112	5	0,225	2 ½	17	89	61
	90	10	729 150 113	4	0,363	3	20	107	71
	110	10	729 150 114	10	0,567	4	28	131	89
	5	140	10	729 150 116	1	1,175	5	32	162
160		10	729 150 117	4	1,713	6	36	185	122
200		10	729 150 119	1	2,546	8	43	225	149
225		10	729 150 120	1	3,162	8	49	250	168
250		6	729 150 121	1	6,139	9	60	282	192
280		6	729 150 122	1	10,500	10	66	318	213
315		6	729 150 123	1	14,600	12	74	356	239

The technical data are not binding. They neither constitute expressly warranted characteristics nor guaranteed properties nor a guaranteed durability. They are subject to modification. Our General Terms of Sale apply.

Georg Fischer Piping Systems Ltd, Postfach, CH-8201 Schaffhausen/Switzerland
 Phone +41 -(0)52-631 1111
 e-mail: info.ps@georgfischer.com
 Internet: <http://www.gfps.com>